



**31,32 SUPPLY GRILLES & REGISTERS**




**CORE STYLES:**

**31 SINGLE DEFLECTION**




**32 DOUBLE DEFLECTION**




**BORDERS:**


**C CURVED FACE**



**F FLAT FACE**



**SF - STEEL FRAME**



- H=1<sup>5</sup>/<sub>16</sub>" (33) - STYLE 31
- H=1<sup>13</sup>/<sub>16</sub>" (46) - STYLE 32

- H=1<sup>1</sup>/<sub>4</sub>" (32) - STYLE 31
- H=2" (51) - STYLE 32

- H=1<sup>5</sup>/<sub>16</sub>" (33) STYLE 31
- H=2<sup>1</sup>/<sub>16</sub>" (52) STYLE 32

**NOTES:**

- STANDARD CONSTRUCTION WITH A MULLION: A MULLION IS PROVIDED WHEN NOMINAL SIZE GRILLE DIMENSIONS EXCEED 20" (508).
- LOUVER BLADES - INDIVIDUALLY ADJUSTABLE.
- TYPE A FASTENING - COUNTERSUNK SCREW HOLES FOR NO.8 S.M.S. PER FACTORY STANDARD. (SCREWS SUPPLIED)
- TYPE H FASTENING-FOR ED APPLICATION PILOT HOLE FOR PAN HEAD SMS. SCREW FACTORY STANDARD (SCREWS SUPPLIED).
- AVAILABLE SIZES:  
MINIMUM - 6" X 4" (152x102)  
MAXIMUM - 36" X 96" (914x2438)  
MAXIMUM - 48" X 48" (1219x1219) WITH SF FRAME
- OVERSIZED UNITS AVAILABLE c/w DUCT MOUNTING CHANNEL.
- BLADE ORIENTATION - FRONT SET  
- L = PARALLEL TO LONG DIMENSION.  
- S = PARALLEL TO SHORT DIMENSION.


ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

<b>PROJECT:</b>		<b>PRICE</b> <sup>®</sup>	
<b>ENGINEER:</b>		<i>MG</i>	<b>31, 32</b> ALUMINUM SUPPLY GRILLES & REGISTERS
<b>CUSTOMER:</b>		222001	
<b>SUBMITTAL DATE:</b>	<b>SPEC. SYMBOL:</b>	2015/10/29	


**31,32 SERIES MOUNTING OPTIONS AND BORDERS**

**BORDERS**

**N - NARROW MARGIN**




**ED EXPOSED DUCT**




ED APPLICATION IS SUPPLIED COMPLETE WITH BORDER AND DUCT MOUNTING FRAME  
 • AVAILABLE WITH TYPE H OR TYPE C FASTENING

**FASTENING**

**A - COUNTER SUNK SCREW**  
C BORDER ILLUSTRATED




**C - CONCEALED BRACKET**  
C BORDER ILLUSTRATED



H-STRAIGHT SCREW HOLES (FOR ED FRAME ONLY)

**MOUNTING FRAMES**



ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

<b>PROJECT:</b>		<b>PRICE</b> <sup>®</sup>	
<b>ENGINEER:</b>		<i>mg</i>	<b>31, 32 SERIES</b>
<b>CUSTOMER:</b>		222001	MOUNTING OPTIONS AND BORDERS
<b>SUBMITTAL DATE:</b>	<b>SPEC. SYMBOL:</b>	2015/10/29	